Beetronics
Bloemstraat 28, 1016LC Amsterdam, Netherlands
+31 20 24 46 365 · info@beetronics.eu

Model: 13TS7

13 Inch Touchscreen

View Product Online









Features

- Full HD multi-touch panel
- Input: HDMI, DisplayPort, USB-C, VGA
- Mounting: Wall, desktop
- External dimensions: 318 x 200 x 34 mm

This Full HD 13 inch touchscreen has a reliable multi-touch panel which ensures accurate operation. The 13TS7 provides crystal-clear image quality with excellent 178° viewing angles and is compatible with Windows, Mac & Linux operating systems. The touchscreen monitor is designed for professional applications and suitable for intensive use.

©2026 Beetronics

Beetronics
Bloemstraat 28, 1016LC Amsterdam, Netherlands
+31 20 24 46 365 · info@beetronics.eu

General

Manufacturer	Beetronics
Product Line	Touchscreen Series
Product Name	13 Inch Touchscreen
Item Number	13TS7
Previous Model	13TS3
Product Type	Touchscreen
Warranty	2 Years
User Manual	Download PDF
Quickstart	Download PDF

Display Architecture

Aspect Ratio	16:9 (4:3 Adjustable)
Native Resolution	1920 x 1080
Pixels Per Inch	166 PPI
Diagonal Size	13.3 Inches (337 mm)
Panel Type	IPS-LCD
Backlight	LED
Surface	Tempered glas
Supported Orientation	Landscape, Portrait, Face-up

Display Performance

Maximum Brightness	300 nits (typical)
Minimum Brightness	1 nit
Contrast	1400:1
Viewing Angle	178° Horizontal, 178° Vertical
Response Time	10 ms
Supported Resolutions	1920 x 1080 (max), 640 x 480 (min)
Colour Encoding System	PAL/NTSC/SECAM

Touch Technology

Touch Technology	Capacitive (PCAP)
Touch Points	10-Point (Multi-Touch)
Touch Interface	USB HID-Compliant
Touch Control	Stylus, Hand, Glove
Gesture Support	Tap, swipe, scroll, pinch-to-zoom (dependent on host system OS and application)

©2026 Beetronics

Beetronics
Bloemstraat 28, 1016LC Amsterdam, Netherlands
+31 20 24 46 365 · info@beetronics.eu

Operational Features

Audio	Dual Integrated Speakers
Auto-On	Automatically powers on when it receives current or a signal.
Dimmable	Adjustable backlight brightness via remote control or optional dimmer.

Software & Compatibility

Windows	Windows 8, 10, 11
Windows Embedded	Windows Embedded 8 Industry, 8.1 Industry, IoT Enterprise
macOS	Tahoe, Sequoia, Sonoma
Linux	All Linux Distributions
Brightsign	All BrightsignOS Versions
Samsung DeX	All Samsung DeX Versions

Connectivity

HDMI	1x
DisplayPort	1x
VGA	1x
USB-C	1x Video, Audio, Touch
USB-A	Via USB-C to USB-A adapter. This only activates the touch functionality and should be combined with HDMI, the DisplayPort, or VGA for image display.
AUX Input (3.5mm)	1x
AUX Output (3.5 mm)	1x

Mechanical

Dimensions (Without Stand)	318 x 200 x 34 mm
Active Area	293 x 167 mm
Weight	1000 Grams (1600 Grams With Stand)
Colour	Black

Mounting

Wall Mount	VESA 75x75mm
Flush Mount	Possible, no accessories available
Stand	Adjustable and Detachable
Supported Mounting Orientations	Landscape, Portrait, Face-up

©2026 Beetronics

Beetronics
Bloemstraat 28, 1016LC Amsterdam, Netherlands
+31 20 24 46 365 · info@beetronics.eu

Power

Input Voltage	19V DC
Operating Voltage Range	9-36V DC
Power Consumption	11 W (On), 0.4 W (Standby)
Power Supply	External DC Power Supply Included
Included Power Adapter	Input: 100-240V AC, 50/60Hz, Output: 19V DC, 1.5A
Power Connector	5.5 mm × 2.1 mm DC Barrel Connector
DC Cable Length	1.5 m
AC Power Cord Length	1.0 m

Environmental

Max. Non-Stop Operating Time	24/7
Operating Humidity	10% - 90% Non-Condensing
Ingress Protection (IP)	IP65 Front Panel
Impact Protection (IK)	IK08
MTBF	50K

Compliance & Regulations

Regional Standards	CE, UKCA, FCC (Part 15), ISED (ICES-003)
Environmental Standards	RoHS, REACH, WEEE, California Proposition 65, Conflict Minerals (3TG; supplier declaration-based)
Industry Standards	Railway: EN 50155, EN 45545-2; Automotive: e-Mark, UN ECE R10, SAE J1113, SAE J1455
Compliance Scope	Standards and certifications apply to the tested product configuration using the specified power supply. Final system-level compliance remains the responsibility of the party responsible for system integration.
Compliance Statement	Download PDF

Package Content

Includes	Touchscreen, USB-C to USB-C Cable, USB-C to USB-A Cable, Stand, Remote Control, Power Adapter, Quickstart

Compatible Accessories

Infrared Extension	Compatible With Infrared Extender (IRC7)
Rack Mounting	Compatible With 19 Inch Rack Mount Kit (RMK2)
Wall Mounting	Compatible With Flat Wall Mount Bracket (VWB1)
Stand	VDK4 Included as Standard
Touch Pen	Compatible With CTS7 Capacitive Touchscreen Stylus

©2026 Beetronics

Beetronics
Bloemstraat 28, 1016LC Amsterdam, Netherlands
+31 20 24 46 365 · info@beetronics.eu

EPR Weights

Plastic Packaging Weight (in Gram)	115
Paper Packaging Weight (in Gram)	567
Other Packaging Weight (in Gram)	2
Transport Packaging Weight (in Gram)	156
Total Packaging Weight (in Gram)	840
WEEE Weight (in Gram)	2000

©2026 Beetronics

Beetronics
Bloemstraat 28, 1016LC Amsterdam, Netherlands
+31 20 24 46 365 · info@beetronics.eu

