




Model: 17TS7M

## 17 Inch Touchscreen Metal

This Full HD 17 inch touchscreen has a reliable multi-touch panel which ensures accurate operation. The 17TS7M delivers best-in-class picture quality with excellent 178° viewing angles and is compatible with Windows, Mac & Linux operating systems. The touchscreen monitor is designed for professional applications, easy to integrate and suitable for intensive use.

- ✓ Full HD multi-touch panel
- ✓ Input: HDMI, DisplayPort, USB-C, VGA
- ✓ Mounting: Flush, embedded, wall, desktop
- ✓ External dimensions: 430 x 263 x 42 mm



## General

Manufacturer	Beetronics
Item Number	17TS7M
Product Name	17 Inch Touchscreen Metal
Warranty	2 Years
User Manual	<a href="#">Download PDF</a>
Quickstart	<a href="#">Download PDF</a>

## Supported Operating Systems

Windows	Windows 8, 10, 11
Windows Embedded	Windows Embedded 8 Industry, 8.1 Industry, IoT Enterprise
macOS	Sequoia, Sonoma, Ventura
Linux	All Linux Distributions
ChromeOS	All ChromeOS Versions
Brightsign	All BrightsignOS Versions
Samsung DeX	All Samsung DeX Versions

## Panel

Diagonal Size	17.2 Inches (438 mm)
Panel Type	IPS-LCD
Aspect Ratio	16:9 (4:3 Adjustable)
Response Time	10 ms
MTBF	50K
Native Resolution	1920 x 1080
Supported Resolutions	1920 x 1080 (max), 640 x 480 (min)
Pixels Per Inch	127 PPI
Backlight	LED
Brightness	300 cd/m2
Contrast	800:1
Colour Encoding System	PAL/NTSC/SECAM
Viewing Angle	178° Horizontal, 178° Vertical
Surface	Tempered glas
Touch Technology	Capacitive, 10-Point Multi-Touch (PCAP)
Touch Control	Stylus, Hand, Glove

## Connectivity

HDMI	1x
DisplayPort	1x
VGA	1x
USB-C	1x Video, Audio, Touch
USB-A	Via USB-C to USB-A adapter. This only activates the touch functionality and should be combined with HDMI, the DisplayPort, or VGA for image display.
AUX Input (3.5mm)	1x
AUX Output (3.5 mm)	1x

## Size & Weight

Colour	Black
Dimensions (Without Stand)	430 x 263 x 42 mm
Active Area	382 x 215 mm
Weight	3600 Grams (4400 Grams With Stand)
Thickness	41 mm

## Features & Functions

Audio	Integrated Speakers
Key-Lock	The control buttons can be blocked.
Auto-On	Automatically powers on when it receives current or a signal.
Dimmable	Adjustable Backlight Brightness
Mirroring	Image can be mirrored, horizontally and vertically
Orientation	Landscape, Portrait, Face-up

## Power

Input Voltage	DC 9-36V
Consumption	Typical 11.8 W (On), 0.4 W (Standby)
Power Supply	External DC (Power Adapter Included)
Power Adapter	Input: AC100-240V, 50/60Hz , Output: 19V-1.5A
Power Adapter Output Connector	DC Barrel Plug 2.1mm x 5.5mm

## Environmental

Max. Non-Stop Operating Time	24/7
Operating Temperature	-20°C to +60°C
Storage Temperature	-20°C to +70°C
Operating Humidity	20% - 85% Non-Condensing

## Mounting

Wall Mount	✔ VESA 100x100mm
Flush Mount	✔ Mounting Strips Included
Stand	✔ Adjustable and Detachable

## Certifications & Standards

IP Rating	IP65 Front Panel
Impact Protection	IK08
Certifications	CE, FCC, RoHS, REACH, WEEE, UKCA, e-Mark, EN50155, EN60601-1, EN60601-1-2, CCC, CAN ICES-003(A)/NMB-003(A)

## Package Content

Includes	Touchscreen, USB Cable, Remote Control, AC Power Adapter, Stand, Installation Strips, Manual
----------	--

## Compatible Accessories

Infrared Extension	<a href="#">Compatible With Infrared Extender (IRC7)</a>
Dimmer	<a href="#">Compatible With External Dimmer (DMK7/DMK8)</a>
Rack Mounting	<a href="#">Compatible With 19 Inch Rack Mount Kit (RMK2)</a>
Wall Mounting	<a href="#">Compatible With Flat Wall Mount Bracket (VWB1)</a>
Stand	<a href="#">Compatible With VDK6 Metal Stand</a>
Touch Pen	<a href="#">Compatible With CTS7 Capacitive Touchscreen Stylus</a>



