

Model: 7HD7


7 inch field monitor

This 7 inch field monitor has a Full HD IPS panel. This ensures a sharp image with vibrant colours and an excellent viewing angle. The monitor supports all common resolutions up to and including 4K and is suitable for every type of camera. The monitor is equipped with both HDMI and AV input and output and comes with a detachable lens hood.

- 1920 x 1200 resolution (Full HD)
- HDMI (input & output), AV (input & output)
- Sunshade & battery connection
- Suitable for any type of camera







© 2024 Beetronics

beetronics

Beetronics
Bloemstraat 28
1016LC Amsterdam
Netherlands

Phone: +31 20 24 46 365
Fax: +31 20 70 08 369
E-mail: info@beetronics.eu
Web: www.beetronics.eu

General

Manufacturer	Beetronics
Item number	7HD7
Previous model	7HD5
Product name	7 inch field monitor
Warranty	2 years

Panel

Diagonal size	7.0 inches (178 mm)
Aspect ratio	16:10 (16:9, 4:3 adjustable)
Native resolution	1920 x 1200
Supported resolutions	2160p, 1080p/1080i, 720p, 576p/576i, 480p/480i
Pixels per inch	324 PPI
Brightness	450 cd/m2
Contrast	1100:1
Color encoding system	PAL/NTSC/SECAM
Viewing angle	178° horizontal, 178° vertical

© 2024 Beetronics

beetronics

Beetronics
Bloemstraat 28
1016LC Amsterdam
Netherlands

Phone: +31 20 24 46 365
Fax: +31 20 70 08 369
E-mail: info@beetronics.eu
Web: www.beetronics.eu

Connectivity

HDMI input	1x
HDMI output	1x
BNC video input (CVBS)	1x
BNC video output (CVBS)	1x
AUX output	1x
Battery	Optional (BP4)

Size & weight

Colour	Black
Weight	400 grams
Height	130 mm
Thickness	35 mm

Features and functions

Audio	Integrated speakers
Auto-on	Automatically powers on when it receives current or a signal
Mirroring	Image can be mirrored, horizontally and vertically
Sunshade	Detachable and foldable

Power

Input voltage	DC 9-33V
Power adapter	Input: AC100-240V, 50/60Hz , Output: 12V-2A

© 2024 Beetronics

beetronics

Beetronics
Bloemstraat 28
1016LC Amsterdam
Netherlands

Phone: +31 20 24 46 365
Fax: +31 20 70 08 369
E-mail: info@beetronics.eu
Web: www.beetronics.eu

Environmental

Operating temperature	-20°C to +60°C
Storage temperature	-20°C to +70°C
Operating humidity	20% - 80% non-condensing

Mounting

Wall mount	VESA (75 mm)
Tripod	1.4" tripod mount screw

Certifications & Standards

Certifications	CE, FCC, RoHS, REACH, WEEE, IC, UKCA, e-Mark, EN50155, EN60601, CCC

Package content


Includes	Monitor, Hotshoe, Sunshade, AC power adapter, Manual

© 2024 Beetronics

beetronics

Beetronics
Bloemstraat 28
1016LC Amsterdam
Netherlands

Phone: +31 20 24 46 365
Fax: +31 20 70 08 369
E-mail: info@beetronics.eu
Web: www.beetronics.eu



© 2024 Beetronics

beetronics

Beetronics
Bloemstraat 28
1016LC Amsterdam
Netherlands

Phone: +31 20 24 46 365
Fax: +31 20 70 08 369
E-mail: info@beetronics.eu
Web: www.beetronics.eu