




Model: 13HD7

13 Inch Monitor

This 13 inch Full HD monitor delivers best-in-class picture quality with excellent 178° viewing angles. The 13 inch monitor has a lightweight housing and is ideal for desktop and wall mounting. The 13HD7 can be connected via HDMI, VGA, BNC or RCA connections.

- ✓ 1920 x 1080 resolution (Full HD)
- ✓ Input: HDMI, VGA, BNC, RCA
- ✓ Mounting: Wall, desktop
- ✓ External dimensions: 318 x 200 x 33 mm



General

Manufacturer	Beetronics
Product Line	Monitor Series
Product Name	13 Inch Monitor
Item Number	13HD7
Previous Model	13HD5
Product Type	Monitor
Warranty	2 Years
User Manual	Download PDF
Quickstart	Download PDF

Display Architecture

Diagonal Size	13.3 Inches (339 mm)
Aspect Ratio	16:9 (4:3 Adjustable)
Native Resolution	1920 x 1080
Pixels Per Inch	166 PPI
Panel Type	IPS-LCD
Backlight	LED
Surface	Anti-Glare Hard Coating (3H)
Supported Orientation	Landscape, Portrait, Face-up

Display Performance

Maximum Brightness	300 nits (typical)
Minimum Brightness	1 nit
Contrast	1400:1
Viewing Angle	178° Horizontal, 178° Vertical
Response Time	10 ms
Supported Resolutions	1920 x 1080 (max), 640 x 480 (min)
Colour Encoding System	PAL/NTSC/SECAM

Operational Features

Audio	Dual Integrated Speakers
USB Media Player	Built-in USB media player with auto-play on power-up and continuous loop playback. Supports common video formats such as: MP4, AVI, MKV, MOV, MPG.
Key-Lock	The control buttons can be blocked.
Auto-On	Automatically powers on when it receives current or a signal.
Dimmable	Adjustable backlight brightness via remote control or optional dimmer.
Mirroring	Teleprompter compatible. Image can be horizontally and vertically mirrored.

Connectivity

HDMI	1x
VGA	1x
BNC (CVBS)	1x
RCA Video	1x
USB-A	1x Integrated USB Media Player
AUX Output (3.5 mm)	1x

Mechanical

Dimensions (Without Stand)	318 x 200 x 33 mm
Image Size	295 x 167 mm
Weight	600 Grams (1000 Grams With Stand)
Colour	Black

Mounting

Wall Mount	✔ VESA 75x75mm
Flush Mount	✔ Possible, no accessories available
Stand	✔ Adjustable and Detachable
Supported Mounting Orientations	Landscape, Portrait, Face-up

Power

Input Voltage	19V DC
Operating Voltage Range	9-36V DC
Power Consumption	12 W (On), 0.4 W (Standby)
Power Supply	External DC Power Supply Included
Included Power Adapter	Input: 100-240V AC, 50/60Hz, Output: 19V DC, 1.5A
Power Connector	5.5 mm x 2.1 mm DC Barrel Connector
DC Cable Length	1.5 m
AC Power Cord Length	1.0 m

Environmental

Max. Non-Stop Operating Time	24/7
Operating Temperature	-10°C to +60°C (14°F to 140°F)
Storage Temperature	-20°C to +70°C (-4°F to 158°F)
Operating Humidity	10% - 90% Non-Condensing
MTBF	50K

Compliance & Regulations

Regional Standards	CE, UKCA, FCC (Part 15), ISED (ICES-003), CCC
Environmental Standards	RoHS, REACH, WEEE, California Proposition 65, Conflict Minerals (3TG; supplier declaration-based)
Industry Standards	Railway: EN 50155, EN 45545-2; Automotive: e-Mark, UN ECE R10, SAE J1113, SAE J1455
Compliance Scope	Standards and certifications apply to the tested product configuration using the specified power supply. Final system-level compliance remains the responsibility of the party responsible for system integration.
Compliance Statement	Download PDF

Package Content

Includes	Monitor, Stand, Remote Control, Power Adapter, Quickstart
----------	---

Compatible Accessories

Rack Mounting	Compatible With 19 Inch Rack Mount Kit (RMK2)
Wall Mounting	Compatible With Flat Wall Mount Bracket (VWB1)
Stand	VDK4 Included as Standard



